

配管パイプ・屋内配管

配管パイプ TP-A (JIS G 3459) SUS304

■単位：kg/m

呼び径	規/勵		1.0	1.2	1.5	2.0	2.5	3.0	3.5	3.7	4.0	4.5	5.0	5.1	5.2	5.5	6.0	6.5	6.6	7.0	7.1	7.6	8.2
A	B	mm																					
		6.0	0.125																				
		8.0	0.174																				
		10.0	0.224	0.318																			
6	1/8	10.5	0.237	0.336	0.423																		
		12.0	0.274	0.392	0.498																		
8	1/4	13.8	0.377	0.460	0.588	0.807																	
		16.0	0.374	0.542	0.697																		
10	3/8	17.3	0.590	0.762	0.922	1.07																	
		19.0	0.448	0.654	0.847																		
		20.0	0.691	0.897																			
15	1/2	21.7	0.755	0.981	1.20	1.40	1.66																
		25.0	0.878	1.15																			
		25.4	0.893	1.17	1.67																		
20	3/4	27.2	0.960	1.26	1.54	1.81																	
		30.0	1.060	1.39	2.02																		
		32.0	1.140	1.49	2.17																		
25	1	34.0	1.210	1.59	1.96	2.32	2.66	2.99															
		38.0	1.360	1.79	2.62																		
32	1 1/4	42.7	1.540	2.03	2.97	3.42	3.85																
40	1 1/2	48.6	1.760	2.32	3.41	3.93	4.44	5.53															
		50.8	1.840	2.43	3.57																		
50	2	60.5	2.200	2.91	4.30	4.97	5.63	7.54															
65	2 1/2	76.3	3.70	5.48	6.35	7.20	8.88	9.21	12.1														
80	3	89.1	4.34	6.43	8.48																		
90	3 1/2	101.6	4.96	7.37	9.72																		
100	4	114.3	5.59	8.32	11.0	13.60	16.2																
125	5	139.8	10.20	11.90	13.5	16.80	21.9																
150	6	165.2	12.10	14.10	16.1	20.00	28.0																
200	8	216.3	15.90	21.2	26.30	34.0	42.5																
250	10	267.4	19.80	26.2	42.2																		
300	12	318.5	23.60	31.3	35.2	50.5																	

※定尺は4,000mm (一部6,000mmもあります)

※上記以外のサイズ・鋼種 (316・316L) については、お問い合わせください。

■ スケジュール5S ■ スケジュール10S ■ スケジュール20S ■ スケジュール10S・20S ■ スケジュール40 ■ スケジュール80

寸法公差基準表

外径	φ30mm未満	±0.3mm	厚み	t 2.0mm未満	±0.2mm
	φ30mm以上	±1%		t 2.0mm以上	±10%

屋内配管 (寸法、外径の許容差及び重量)

JISG 3448 SUS304TP-D, SUS316TP-D

■単位：mm

呼び方		外径	長さ	外径の許容差	厚み	重量 kg/m	
Su	A・Su(1)					304	316
13	-	15.88	4,000	0	0.8	0.301	0.303
20	-	22.22	〃	0	1.0	0.529	0.532
25	-	28.58	〃	0	1.0	0.687	0.691
30	25	34.00	〃	±0.20mm	1.2	0.980	0.986
40	32	42.70	〃	±0.20mm	1.2	1.240	1.250
50	40	48.60	〃	±0.25mm	1.2	1.420	1.430
60	50	60.50	〃	±0.25mm	1.5	2.200	2.210
75	65	76.30	〃	±1%	1.5	2.790	2.810

呼び方		外径	長さ	外径の許容差	厚み	重量 kg/m	
Su	A・Su(1)					304	316
80	-	89.1	4,000	±1%	2.0	4.34	4.37
100	-	114.3	〃	±1%	2.0	5.59	5.63
125	-	139.8	〃	±1%	2.0	6.87	6.91
150	-	165.2	〃	±1%	3.0	12.10	12.20
200	-	216.3	〃	±1%	3.0	15.90	16.00
250	-	267.4	〃	±1%	3.0	19.80	19.90
300	-	318.5	〃	±1%	3.0	23.60	23.80

■は受注生産

注(1) 呼び方A・Suは、JIS G 3542 (配管用炭素鋼鋼管) の呼び方Aに準じたもので、当分の間は併用しても差し支えないものである。

試験圧力：水圧25kgf/cm²