

フラットバー

■=受注生産 ◆=在庫かぎり ★=メーカー取寄 HL=HL 4=#400 C=コールド ●=酸洗仕上

フラットバー SUS304・316・316L

■単位：mm

サイズ 厚さ×幅	長さ	kg/P	コールド	HL	#400	スリット ホット	セミ ホット	熱間圧延	
								304	316 316L
2×6	2,000	0.190	C						
8	//	0.254	C						
10	4,000	0.636	C						
12	//	0.760	C						
15	//	0.952	C			■			
20	//	1.270	C			■			
25	//	1.580	C			■			
30	//	1.900	C			■			
32	//	2.030	C			■			
38	//	2.410				■			
40	//	2.540	C			■			
50	//	3.170	C			■			
3×5	4,000	0.476	C						
6	//	0.572	C						
8	//	0.760	C						
9	//	0.856	C						
10	//	0.952		HL		■	■		
12	//	1.140		HL		■	■		
13	//	1.240		HL		■	■		
15	//	1.430		HL	4	■	■		
16	//	1.520		HL					
19	//	1.810		HL		■	■		
20	//	1.900		HL	4	■	■		
22	//	2.090		HL		■	■		
25	//	2.380		HL	4	■	■		
30	//	2.860		HL	4	■	■		
32	//	3.040		HL	4	■	■		
35	//	3.330		HL		■			
38	//	3.620		HL	4	■	■		
40	//	3.810		HL	4	■	■		
42	//	4.000		HL					
45	//	4.280		HL		■			
50	//	4.760		HL	4	■	■		
60	//	5.720		HL	4	■	■		
65	//	6.200		HL		■			
75	//	7.120		HL		■	■		
100	//	9.520		HL		■	■		
110	//	10.500		HL					
120	//	11.400		HL					
125	//	11.900		HL					
130	//	12.400		HL					
140	//	13.300		HL					
150	//	14.300		HL					
4×9	4,000	1.140	C						
10	//	1.270		HL					

サイズ 厚さ×幅	長さ	kg/P	コールド	HL	#400	スリット ホット	セミ ホット	熱間圧延	
								304	316 316L
11	4,000	1.40		HL					
13	//	1.65		HL					
15	//	1.90		HL	4	■	■		
16	//	2.03		HL					
19	//	2.41		HL		■			
20	//	2.54		HL	4	■	■	●	
22	//	2.79		HL		■		●	
25	//	3.17	3.19	HL	4	■	■	●	●
30	//	3.81	3.83	HL	4	■	■	●	●
32	//	4.08		HL	4	■	■	●	
35	//	4.44		HL				●	
38	//	4.84		HL	4	■	■	●	
40	//	5.08	5.12	HL	4	■	■	●	●
45	//	5.72		HL		■		●	
50	//	6.36	6.40	HL	4	■	■	●	●
60	//	7.60		HL		■		●	
65	//	8.24		HL		■	■	●	
75	//	9.52		HL		■	■	●	
90	//	11.4		HL				●	
100	//	12.7		HL		■			
5×8	4,000	1.27		C					
9	//	1.43		C					
10	//	1.58		HL					
12	//	1.90		HL					
13	//	2.06		HL					
15	//	2.38		HL	4	■	■		
16	//	2.54		HL					
19	//	3.01		HL		■	■	●	
20	//	3.17	3.19	HL	4	■	■	●	●
22	//	3.49		HL				●	
25	//	3.96	3.99	HL	4	■	■	●	●
30	//	4.76	4.80	HL	4	■	■	●	●
32	//	5.08		HL	4	■		●	
35	//	5.56		HL		■		●	
38	//	6.04		HL	4	■		●	
40	//	6.36	6.40	HL	4	■	■	●	●
50	//	7.92	8.00	HL	4	■	■	●	●
60	//	9.52		HL		■		●	
65	//	10.3		HL		■	■	●	
75	//	11.9		HL		■	■	●	
90	//	14.3		HL		■		●	
100	//	15.8		HL		■	■	●	
130	//	20.6		HL					
150	//	23.8		HL					

フラットバー


フラットバー SUS304・316・316L

■単位：mm


サイズ 厚さ×幅	長さ	kg/P		コールド	HL	#400	スリット ホット	セミ ホット	熱間圧延	
		304	316 316L						304	316 316L
6× 9	4,000	1.71		C						
10	//	1.90			HL					
12	//	2.28			HL					
13	//	2.48			HL					
15	//	2.86			HL	4	■	■		
16	//	3.04			HL					
18	//	3.42			HL					
19	//	3.62			HL		■		●	
20	//	3.81	3.83		HL	4	■	■	●	◆*1
22	//	4.20			HL		■		●	
25	//	4.76	4.80		HL	4	■	■	●	●
30	//	5.72	5.76		HL	4	■	■	●	●
32	//	6.08	6.12		HL	4	■	■	●	●
35	//	6.68			HL		■		●	
38	//	7.24	7.28		HL	4	■	■	●	●
40	//	7.60	7.68		HL	4	■	■	●	●
42	//	8.00			HL					
45	//	8.56			HL	4	■	■	●	
50	4,000	9.52	9.56		HL	4	■	■	●	●
	6,000	14.30			HL		■		●	
60	4,000	11.40			HL	4	■	■	●	
65	4,000	12.40	12.4		HL	4	■	■	●	●
	6,000	18.50			HL		■		●	
70	4,000	13.30			HL		■	■	●	
75	4,000	14.30	14.4		HL	4	■	■	●	●
	6,000	21.40			HL		■		●	
90	4,000	17.10			HL		■	■	●	
100	4,000	19.00	19.2		HL	4	■	■	●	●
	6,000	28.60			HL		■		●	
110	4,000	20.90			HL		■			
120	//	22.80			HL		■			
125	//	23.80			HL		■			
130	//	24.80			HL		■			
140	//	26.60			HL		■			
150	//	28.60			HL		■			

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	#400	熱間圧延	
		304	316 316L				304	316 316L
7× 20	4,000	4.44						●
8× 10	4,000	2.54		C	HL			
	16	//	4.08	C	HL			●
25	//	6.36						●
30	//	7.60						●
32	//	8.12		C	HL			●
38	//	9.64		C	HL			●
40	//	10.20						●
45	//	11.40						●
50	//	12.70		C	HL			●
65	//	16.50						●
75	//	19.00						●
100	//	25.40						●
9× 13	4,000	3.71		C	HL			
	15	//	4.28	C	HL			●
16	//	4.56		C	HL			●
19	//	5.44		C	HL			●
20	//	5.72		C	HL	4		●
22	//	6.28		C	HL			●
25	4,000	7.12	7.20	C	HL	4		●
	6,000	10.70		C	HL			●
30	4,000	8.56	8.60	C	HL	4		●
	6,000	12.80		C	HL			●
32	4,000	9.12	9.20	C	HL	4		●
	6,000	13.70		C	HL			●
35	4,000	10.00						●
38	4,000	10.80	10.9	C	HL	4		●
	6,000	16.30		C	HL			●
40	4,000	11.40		C	HL	4		●
	6,000	17.10		C	HL			●
45	4,000	12.80						●
50	4,000	14.30	14.4	C	HL	4		●
	6,000	21.40		C	HL			●
55	4,000	15.70						●
60	//	17.10		C	HL			●
65	4,000	18.60	18.7	C	HL	4		●
	6,000	27.80		C	HL			●
75	4,000	21.40	21.6	C	HL	4		●
	6,000	32.10		C	HL			●
90	4,000	25.70	25.8	C	HL			●
100	4,000	28.60	28.7	C	HL			●
	6,000	42.80		C	HL			●
125	4,000	35.70		C	HL			●
	6,000	53.50						●

- ◎スリットホットフラットバー *1=316Lのみ
 No.1コイルをスリットカットし、圧延後ショットを施したフラットバー。
 (2t全てと6t×110幅以上はショットなし)
- ◎セミホットフラットバー
 No.1コイルをスリットカットし、圧延を施したフラットバー。



スリットホットフラットバー



セミホットフラットバー

※熱間圧延品はJIS G4303

※9×19~9×100=製造方法により公差が異なります。

フラットバー

■=受注生産 ◆=在庫かぎり ★=メーカー取寄 HL=HL 4=#400 C=コールド ●=酸洗仕上

フラットバー SUS304・316・316L

■単位：mm

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	熱間圧延		
		304	316 316L			304	316 316L	
150	4,000	42.80		C	HL	●		
	6,000	64.20				●		
200	4,000	57.20		C	HL	●		
250	//	71.20		C		●		
300	//	85.60		C		●		
10x	15	4,000	4.76	C	HL	●		
	19	//	6.04	C	HL	●		
	20	//	6.36	C	HL	●		
	25	//	7.92	C	HL	●		
	30	//	9.52		C	HL	●	
	32	//	10.20		C	HL	●	
	35	//	11.10				●	
	38	//	12.00		C		●	
	40	//	12.70		C	HL	●	
	50	//	15.80	16.0	C	HL	●	●
	65	//	20.60		C	HL	●	
	75	//	23.80		C	HL	●	
	100	//	31.70	31.9	C		●	●
	125	//	39.60		C		●	
	150	//	47.60		C	HL	●	
	200	//	63.60		C		●	
	250	//	79.20		C		●	
300	//	95.20		C		●		
12x	14	4,000	5.32	C				
	15	//	5.72			●		
	16	//	6.08		C	HL		
	19	//	7.24		C		●	
	20	//	7.60		C	HL	●	
	25	//	9.52	9.56	C	HL	●	●
	28	//	10.60				●	
	30	//	11.40		C	HL	●	
	32	4,000	12.20	12.2	C	HL	●	●
		6,000	18.30		C	HL		
	35	4,000	13.30		C	HL	●	
	38	4,000	14.50	14.6	C	HL	●	●
		6,000	21.70		C	HL	●	
	40	4,000	15.20		C	HL	●	
		6,000	22.90		C	HL		
	45	4,000	17.10				●	
	50	4,000	19.00	19.2	C	HL	●	●
6,000		28.60		C	HL	●		
65	4,000	24.80	24.9	C	HL	●	●	
	6,000	37.10		C	HL	●		
70	4,000	26.60				●		
75	4,000	28.60	28.7	C	HL	●	●	

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	熱間圧延		
		304	316 316L			304	316 316L	
75	6,000	42.80		C	HL	●		
	90	4,000	34.20	C	HL	●		
100	4,000	38.10	38.3	C	HL	●	●	
	6,000	57.10		C	HL	●		
125	4,000	47.60		C	HL	●		
	6,000	71.40				●		
150	4,000	57.20		C		●		
	6,000	85.80				●		
200	4,000	76.00		C		●		
250	//	95.20		C		●		
300	//	114.00		C		●		
16x	19	4,000	9.64	C				
	20	//	10.20	C		●		
	25	//	12.70	12.8	C		●	●
	30	//	15.20				●	
	32	//	16.20	16.4	C	HL	●	●
	35	//	17.80				●	
	38	//	19.30	19.4	C	HL	●	●
	40	//	20.30		C	HL	●	
	50	4,000	25.40	25.5	C	HL	●	●
		6,000	38.00				●	
	65	4,000	33.00	33.2	C	HL	●	●
		6,000	49.50				●	
	75	4,000	38.10	38.3	C	HL	●	●
		6,000	57.10				●	
	90	4,000	45.60				●	
	100	4,000	50.80	51.2	C	HL	●	●
		6,000	76.20				●	
125	4,000	63.60		C	HL	●		
	6,000	95.40				●		
150	4,000	76.00		C		●		
	6,000	114.00				●		
200	4,000	102.00		C		●		
250	//	127.00		C		●		
300	//	152.00		C		●		
19x	25	4,000	15.10	C		●		
	30	//	18.10			●		
	32	//	19.30		C	HL	●	
	35	//	21.10				●	
	38	//	22.90		C	HL	●	
	40	//	24.10				●	
	50	//	30.10	30.3	C	HL	●	●
	65	//	39.20	39.4	C	HL	●	●
	75	//	45.20	45.6	C	HL	●	●
	90	//	54.40				●	

フラットバー

フラットバー SUS304・316・316L

■単位：mm

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	熱間圧延	
		304	316 316L			304	316 316L
100	4,000	60.4	60.8	C	HL	●	●
125	//	75.2		C	HL	●	
150	//	90.4		C		●	
200	//	120.0		C		●	
250	//	151.0		C		●	
300	//	181.0		C		●	
22x 25	4,000	17.4				●	
30	//	20.9				●	
32	//	22.3		C		●	
35	//	24.4				●	
38	//	26.5		C		●	
40	//	27.9				●	
45	//	31.4				●	
50	//	34.9		C		●	
65	//	45.2		C		●	
75	//	52.4		C		●	
100	//	69.6		C		●	
125	//	87.2				●	
150	//	105.0				●	
200	//	140.0				●	
250	//	174.0				●	
300	//	209.0				●	
25x 32	4,000	25.4		C		●	
38	//	30.1		C		●	
40	//	31.7				●	
50	//	39.6		C		●	
60	//	47.6				●	
65	//	51.6		C		●	
75	//	59.6		C		●	
100	//	79.2		C		●	
125	//	99.2		C		●	
150	//	119.0		C		●	
200	//	158.0		C		●	
250	//	198.0				●	
300	//	238.0				●	
30x 50	4,000	47.6		C		●	
55	//	52.4		C		●	
65	//	62.0		C		●	
75	//	71.2		C		●	
100	//	95.2		C		●	
125	//	119.0				●	
150	//	143.0				●	
200	//	190.0				●	

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	熱間圧延	
		304	316 316L			304	316 316L
250	4,000	238.0				●	
300	//	286.0				●	
35x 50	4,000	55.6		C		●	
55	//	61.2				●	
65	//	72.0		C		●	
75	//	83.2		C		●	
100	//	111.0		C		●	
125	//	139.0				●	
150	//	166.0				●	
40x 50	4,000	63.6				●	
65	//	82.4				●	
75	//	95.2				●	
100	//	127.0				●	
125	//	158.0				●	
150	//	190.0				●	
50x 65	4,000	103.0				●	
75	//	119.0				●	
100	//	158.0				●	
125	//	198.0				●	
150	//	238.0				●	
60x 75	4,000	143.0				●	
100	//	190.0				●	
125	//	238.0				●	
150	//	286.0				●	
70x 100	4,000	222.0				●	
125	//	278.0				●	
150	//	333.0				●	
80x 100	4,000	254.0				●	
125	//	317.0				●	
150	//	381.0				●	
90x 125	4,000	357.0					◆
100x125	4,000	396.0				●	
150	//	476.0				●	

※熱間圧延品はJIS G4303

角棒・ラウンドフラットバー

■=受注生産 ◆=在庫かぎり ★=メーカー取寄 HL=HL 4=#400 C=コールド ●=酸洗仕上

角棒 SUS304・316・316L

■単位：mm

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	冷間 圧延	熱間圧延	
		304	316 316L				304	316 316L
3x 3	2,000	0.142		C				
4x 4	4,000	0.508		C				
5x 5	4,000	0.792		C	HL			
6x 6	4,000	1.140		C	HL			
7x 7	4,000	1.560		C	HL			
8x 8	4,000	2.030		C	HL			
9x 9	4,000	2.570		C	HL			
10x 10	4,000	3.170		C	HL	●		
12x 12	4,000	4.560		C	HL	●		
13x 13	4,000	5.360		C	HL	●		
14x 14	4,000	6.200		C		●		
15x 15	4,000	7.120		C	HL	●		
16x 16	4,000	8.120		C	HL	●	●	
19x 19	4,000	11.400	11.5	C			●	●
20x 20	4,000	12.700	12.8	C	HL		●	●
22x 22	4,000	15.400	15.4	C	HL		●	●
25x 25	4,000	19.800	20.0	C	HL		●	●
26x 26	4,000	21.400		C				
28x 28	4,000	24.900		C			●	
30x 30	4,000	28.600	28.7	C			●	●
32x 32	4,000	32.500	32.7	C			●	●
36x 36	4,000	41.200		C			●	
38x 38	4,000	46.000	46.0	C			●	●
40x 40	4,000	50.800		C			●	
42x 42	4,000	56.000	56.4				●	●
45x 45	4,000	64.400		C			●	
50x 50	4,000	79.200	79.8	C			●	●
55x 55	4,000	96.000		C			●	
60x 60	4,000	114.000		C			●	
65x 65	4,000	134.000		C			●	
70x 70	4,000	156.000					●	
75x 75	4,000	178.000					●	
90x 90	4,000	257.000					●	
100x 100	4,000	317.000					●	

※熱間圧延品はJIS G4303

◎熱間圧延フラットバー

高温に加熱してから圧延し、熱処理・ショット酸洗を施したフラットバー。

◎冷間圧延フラットバー

加熱せずに圧延し、熱処理・ショット酸洗を施したフラットバー。

ラウンドフラットバー SUS304

■単位：mm

サイズ 厚さ×幅	長さ	kg/P	研磨
3× 15	4,000	1.36	HL
3× 20	4,000	1.84	HL
3× 25	4,000	2.32	HL
3× 30	4,000	2.79	HL
3× 32	4,000	2.98	HL
3× 40	4,000	3.74	HL
3× 50	4,000	4.72	HL
3× 65	4,000	6.12	HL
3× 75	4,000	7.08	HL
3× 100	4,000	9.48	HL
6× 25	4,000	4.48	HL
6× 30	4,000	5.44	HL
6× 40	4,000	7.36	HL
6× 50	4,000	9.24	HL
6× 65	4,000	12.10	HL
6× 75	4,000	14.00	HL
■ 6× 100	4,000	18.80	HL
■ 9× 30	4,000	8.00	HL
9× 40	4,000	10.80	HL
9× 50	4,000	13.70	HL
■ 9× 65	4,000	18.00	HL
9× 75	4,000	20.80	HL
9× 100	4,000	28.00	HL



3mmは全て1.5R
6mmは全て3R
9mmは全て4.5R

